

**Special features**

- Including connecting cable

|                                      |   |
|--------------------------------------|---|
| <b>Housing Material</b>              | Stainless steel, Die-cast aluminium     |
| <b>Housing Color</b>                 | Silver                                  |
| <b>Material of Lens</b>              | Glass                                   |
| <b>Colour of Lens</b>                | White                                   |
| <b>Protection Class</b>              | Protection class I/protective grounding |
| <b>Rated Input</b>                   | 7.1 W                                   |
| <b>Rated Input Voltage min./max.</b> | 220-240 V/AC 50 / 60 Hz                 |
| <b>Frequency</b>                     |   |
| <b>Power Supply Unit incl.</b>       | Yes                                     |
| <b>Connection Cable Primary</b>      | Yes                                     |
| <b>Primary Connection</b>            | Connection box                          |
| <b>Primary Cable Length</b>          | 1 m                                     |
| <b>Control</b>                       | No                                      |
| <b>Motion Detector</b>               | No                                      |

|   |                                  |
|---|----------------------------------|
| <b>Light Source</b>                     | LED, Light source not changeable |
| <b>Color Temperature</b>                | 3000 K                           |
| <b>Colour Consistency</b>               | 6 SDCM                           |
| <b>Colour Rendering Index (Ra)</b>      | 80                               |
| <b>Rated Luminous Flux</b>              | 85 lm                            |
| <b>Luminous Efficiency</b>              | 35735 lm/W                       |
| <b>Rated Angle of Reflection</b>        | 120 Degree                       |
| <b>Light Distribution</b>               | Symmetric                        |
| <b>Distribution Characteristic 120°</b> | DLS                              |

|                              |        |
|------------------------------|--------|
| <b>Light Exit Surfaces</b>   | 1      |
| <b>Light characteristics</b> | Direct |
| <b>Light direction</b>       | Top    |

|                           |        |
|---------------------------|--------|
| <b>Depth</b>              | 328 mm |
| <b>Width</b>              | 63 mm  |
| <b>Height</b>             | 65 mm  |
| <b>Installation Depth</b> | 90 mm  |
| <b>Cut Out Length</b>     | 313 mm |

|                                |              |
|--------------------------------|--------------|
| <b>Cut Out Width</b>           | 58 mm        |
| <b>Product weight</b>          | 1572 g       |
| <b>Working Temperature</b>     | -20 to 40 °C |
| <b>Storage Temperature</b>     | -10 to 60 °C |
| <b>IP Protection Class</b>     | IP 67        |
| <b>Load Force max.</b>         | 20 kN        |
| <b>Life Time L70 / B50</b>     | 25000 h      |
| <b>Switching Cycles</b>        | 100000       |
| <b>Power Consumption</b>       | 7 kWh/1000h  |
| <b>Energy Efficiency Class</b> | G            |