



- Special features**
- Including 0.5 m connecting cable

<b>Housing Material</b>	Stainless steel, Die-cast aluminium
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	12.2 W
<b>Rated Input Voltage min./max.</b>	220-240 V/AC 50 / 60 Hz
<b>Frequency</b>	
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	Connection box
<b>Primary Cable Length</b>	0.5 m
<b>Control</b>	No
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 67
<b>Load Force max.</b>	5 kN
<b>Life Time L70 / B50</b>	25000 h
<b>Switching Cycles</b>	100000
<b>Power Consumption</b>	13 kWh/1000h
<b>Energy Efficiency Class</b>	G

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	860 lm
<b>Luminous Efficiency</b>	70.49 lm/W
<b>Rated Angle of Reflection</b>	20 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic</b>	DLS
<b>120°</b>	

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Top

<b>Height</b>	42 mm
<b>Diameter</b>	173 mm
<b>Installation Depth</b>	42 mm
<b>Cut Out Diameter</b>	150 mm
<b>Product weight</b>	1612 g