



Small, fine, elegant and discreet - The ACAMAR is a light manufactured from high-quality aluminium. The colour reproduction value is over 90, which means high colour authenticity. The design is chic and interesting thanks to the rounding on one side. You can mount the light with the rounding upwards or downwards, depending on your preference. The white paint inside accentuates the warm white light and ensures pleasant scattering upwards and downwards. The outside is highly polished for an incredible shine.

Special features

- Very high colour reproduction value
- High light emission angle

Housing Material	Die-cast aluminium	Energy Efficiency Class	G
Housing Color	Black		
Protection Class	Protection class I/ protective grounding		
Rated Input	6.9 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	250 lm		
Rated Angle of Reflection	104 Degree		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Depth	170 mm		
Width	100 mm		
Height	80 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 20		
Life Time L70 / B50	30000 h		
Switching Cycles	100000		
Power Consumption	7 kWh/1000h		