



The elegant APODIS wall light captivates with its high-quality aluminium housing with compact base and a fine two-colour coating in black and gold. The Apodis emits powerful warm white light both upwards and downwards via the double light output. The light can be dimmed flexibly using leading/trailing phase angles.

Special features

- Exceptional design
- Dimmable
- High colour reproduction value

Housing Material	Aluminium	Switching Cycles	100000
Housing Color	Rosé	Power Consumption	11 kWh/1000h
Protection Class	Protection class I/ protective grounding	Energy Efficiency Class	G
Rated Input	10.8 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	350 lm		
Rated Angle of Reflection	40 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Below, Top		
Depth	76 mm		
Width	61 mm		
Height	500 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 20		
Life Time L70 / B50	25000 h		