



Whether as a wall light with indirect lighting or with a gooseneck, with a narrow light emission angle of 25°, anyone else in the bed can sleep peacefully while the person on the other side is still reading. The BRAHE also impresses with its simple design in other areas too such as reading corners.

Special features

- Can be rotated and swivelled
- Small light emission angle

Housing Material	Aluminium
Housing Color	Black
Protection Class	Protection class II/protective insulation
Rated Input	3.3 W
Rated Input Voltage min./max. Frequency	100-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Control	No
Motion Detector	No

Switching Cycles	100000
Power Consumption	4 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	165 lm
Rated Angle of Reflection	25 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	360 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Depth	310 mm
Height	80 mm
Diameter	25 mm

Working Temperature	0 to 60 °C
Storage Temperature	0 to 60 °C
IP Protection Class	IP 20

Life Time L70 / B50	30000 h
----------------------------	---------

