



This pendant lamp is distinct for its transparent luminous element. The surface is almost completely see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare. This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light stands out in any type of office environment.

Special features

- Very low glare value
- Transparent luminous element
- Max. suspended mounting 1,500 mm

Housing Material	Aluminium	Life Time L70 / B50	50000 h
Housing Color	Aluminum	Switching Cycles	12500
Material of Lens	Acryl	Power Consumption	54 kWh/1000h
Protection Class	Protection class I/ protective grounding	Energy Efficiency Class	E
Rated Input	53.7 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	6776 lm		
Rated Angle of Reflection	150 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Top, Below		
Height	12.5 mm		
Diameter	580 mm		
Pendulum Length max.	1000 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 40 °C		
IP Protection Class	IP 20		