



LUCEA series pendant lamps are available in 10, 15 and 20 W versions and offer up to 2,000 lumens light output. The maximum suspended mounting is 1,800 mm. Using optional lenses, the light emission angle of the individual models can be narrowed or expanded. Lucea lights feature a die-cast aluminium housing

Special features

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Max. suspended mounting 1,800 mm
- Dimmable

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	PMMA
Protection Class	Protection class I/ protective grounding
Rated Input	15 W
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Control	Leading-edge dimmer, Trailing edge dimmer
Motion Detector	No

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	15 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	1460/1500 lm
Rated Luminous Flux 2	1500 lm
Rated Angle of Reflection	36 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	178 mm
Diameter	85 mm
Pendulum Length max.	1800 mm

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 65 °C
IP Protection Class	IP 20