



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

#### Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser
- Suspended mounting up to 1,800 mm

<b>Housing Material</b>	Aluminium	<b>IP Protection Class</b>	IP 20
<b>Housing Color</b>	Black	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Surface</b>	Matt	<b>Switching Cycles</b>	20000
<b>Material of Lens</b>	Acryl	<b>Power Consumption</b>	30 kWh/1000h
<b>Surface Structure of Lens</b>	Satined	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Protection Class</b>	Protection class I/ protective grounding		
<b>Rated Input</b>	30 W		
<b>Rated Input Voltage min./max. Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	Leading-edge dimmer, Trailing edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	2000/2100 lm		
<b>Rated Luminous Flux 2</b>	2100 lm		
<b>Rated Angle of Reflection</b>	150 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Height</b>	85 mm		
<b>Diameter</b>	400 mm		
<b>Pendulum Length max.</b>	1800 mm		
<b>Working Temperature</b>	-10 to 45 °C		
<b>Storage Temperature</b>	-10 to 45 °C		