



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser
- Suspended mounting up to 1,800 mm

Housing Material	Aluminium	IP Protection Class	IP 20
Housing Color	White	Life Time L70 / B50	30000 h
Housing Surface	Matt	Switching Cycles	20000
Material of Lens	Acryl	Power Consumption	42 kWh/1000h
Surface Structure of Lens	Satined	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Protection Class	Protection class I/ protective grounding		
Rated Input	42 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3000/3100 lm		
Rated Luminous Flux 2	3100 lm		
Rated Angle of Reflection	150 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Height	110 mm		
Diameter	600 mm		
Pendulum Length max.	1800 mm		
Working Temperature	-10 to 45 °C		
Storage Temperature	-10 to 45 °C		