



SLIM series lights include single-luminaire and triple-luminaire pendant lamps and matching pendant lamps for the DEKO-LIGHT current track system. The light body in die-cast aluminium is always the same size (300 x 39 mm). Several SLIM models therefore can also be combined with each other in larger spaces. The pendant lamps for ceiling installation with max. 180 cm suspended mounting are available in a one or three-luminaire variant; three-luminaire variant both with long or round base depending on the arrangement of the lights.

Special features

- Die-cast aluminium
- Fabric cable
- Particularly glare-free thanks to low UGR value
- Suspended mounting up to 1800 mm

Housing Material	Aluminium
Housing Color	Black
Material of Lens	PMMA
Colour of Lens	Transparent
Surface Structure of Lens	Structured
Protection Class	Protection class I/protective grounding
Rated Input	5 W
Rated Input Voltage min./max.	200-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Type	Clamp
Control	No
Motion Detector	No

IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	5 kWh/1000h
Energy Efficiency Class	E

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	500 lm
Rated Angle of Reflection	24 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	300 mm
Diameter	39 mm
Pendulum Length max.	1800 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-20 to 65 °C