



Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.

Special features

- Can be rotated and swivelled via joints
- Dimmable in 3 stages using touch sensor
- High luminous flux
- Ready to use

| | | | |
|--------------------------------------|---|--------------------------------|--------------|
| Housing Material | Aluminium | IP Protection Class | IP 20 |
| Housing Color | White | Life Time L70 / B50 | 25000 h |
| Material of Lens | Plastic | Switching Cycles | 12500 |
| Protection Class | Protection class II/protective insulation | Power Consumption | 10 kWh/1000h |
| Rated Input | 12 W | Energy Efficiency Class | G |
| Rated Input Voltage min./max. | 100-240 V/AC 50 / 60 Hz | | |
| Frequency | | | |
| Power Supply Unit incl. | Yes | | |
| Connection Cable Primary | Yes | | |
| Primary Connection | Power plug | | |
| Primary Cable Length | 1.6 m | | |
| Control | Touch and Dim | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 950 lm | | |
| Luminous Efficiency | 80 lm/W | | |
| Rated Angle of Reflection | 120 Degree | | |
| Swivel Angle | 135 Degree | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Depth | 355 mm | | |
| Diameter | 150 mm | | |
| Product weight | 1460 g | | |
| Working Temperature | -5 to 40 °C | | |
| Storage Temperature | -20 to 50 °C | | |