



<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Blue
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Operating Mode</b>	Voltage constant
<b>Rated Input</b>	2.2 W
<b>Rated Input Voltage</b>	3.7 V/DC
<b>Power Supply Unit incl.</b>	No
<b>Connection Type</b>	USB type C
<b>Control</b>	Touch and Dim
<b>Motion Detector</b>	No
<b>Accumulator/Battery Operated</b>	Yes
<b>Rechargeable/battery included</b>	Yes
<b>Number of Accumulator/Battery</b>	1
<b>Type of Accumulator/Battery</b>	Li-Ion battery type 18650
<b>Accumulator/Battery Capacity</b>	4400 mAh
<b>Accumulator/Battery Voltage</b>	3.7 V/DC
<b>Accumulator Charging Time</b>	5-7 h
<b>Accumulator Operating Time</b>	12 h

<b>Product weight</b>	355 g
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-40 to 60 °C
<b>IP Protection Class</b>	IP 54
<b>Life Time L70 / B50</b>	30000 h
<b>Switching Cycles</b>	15000
<b>Power Consumption</b>	3 kWh/1000h

<b>Light Source</b>	LED, Light source not changeable
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	196 lm
<b>Luminous Efficiency</b>	89.09 lm/W
<b>Rated Angle of Reflection</b>	47 Degree
<b>Light Distribution</b>	Asymetric
<b>Distribution Characteristic 120°</b>	DLS
<b>Height</b>	30 mm
<b>Diameter</b>	120 mm