



Housing Material	Die-cast aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input	2.2 W
Rated Input Voltage	3.7 V/DC
Power Supply Unit incl.	No
Connection Type	USB
Control	Touch and Dim
Motion Detector	No
Accumulator/Battery Operated	Yes
Rechargeable/battery included	Yes
Number of Accumulator/Battery	1
Type of Accumulator/Battery	Li-Ion battery type 18650
Accumulator/Battery Capacity	4400 mAh
Accumulator/Battery Voltage	3.7 V/DC
Type of Accumulator/Battery 2	Li-Ion battery type 18650
Accumulator/Battery Capacity 2	2200 mAh
Accumulator/Battery Voltage 2	3.7 V/DC
Number of Accumulator/Battery 2	1
Accumulator Charging Time	5-7 h
Accumulator Operating Time	10 h

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Depth	175 mm
Width	92 mm
Height	330 mm
Product weight	1450 g
Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 60 °C
IP Protection Class	IP 54
Life Time L70 / B50	30000 h
Switching Cycles	15000

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	212 lm
Luminous Efficiency	96.36 lm/W
Rated Angle of Reflection	50 Degree