



Especially when it comes to lighting house entrances, patios or other access paths, spotlights specially designed for outdoors are the way to go. The protection classes required for such are part and parcel and different colours and shapes are options. Universal use and not to be overlooked as a security product.

<b>Housing Material</b>	Die-cast aluminium	<b>IP Protection Class</b>	IP 44
<b>Housing Color</b>	White	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Surface</b>	Matt	<b>Switching Cycles</b>	15000
<b>Material of Lens</b>	Plastic	<b>Power Consumption</b>	11 kWh/1000h
<b>Surface Structure of Lens</b>	Transparent	<b>Energy Efficiency Class</b>	G
<b>Protection Class</b>	Protection class I/ protective grounding		
<b>Rated Input</b>	11 W		
<b>Rated Input Voltage min./max. Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	Leading-edge dimmer, Trailing edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	730 lm		
<b>Rated Angle of Reflection</b>	35 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Depth</b>	85 mm		
<b>Width</b>	85 mm		
<b>Height</b>	99 mm		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		