



The 3-in-1 ceiling light - with the Helen, you get three lights in one. The LEDs can be switched from warm white to neutral white or cold white using a small switch on the printed circuit board. Thanks to IP54, the ceiling light is suitable for all areas of the home, such as the kitchen, bathroom, living areas and even outdoors. The same light in both the garage and kitchen? No problem with the Helen. Whilst you would probably prefer cold white in the garage, warm white is the top pick for living areas and usually neutral white in the kitchen and bathroom. All bases are covered with just one light.

Special features

- Light colour adjustable in 3 stages
- Splash water protected

Housing Material	Plastic
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Polycarbonate - PC
Colour of Lens	White
Surface Structure of Lens	Satined

Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	20 kWh/1000h
Energy Efficiency Class	G

Protection Class	Protection class II/protective insulation
Rated Input	20 W
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Type	Clamp
Control	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000/4000/5500 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1800 lm
Rated Angle of Reflection	115 Degree
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	89 mm
Diameter	351 mm

Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 54

