



Especially when it comes to lighting house entrances, patios or other access paths, spotlights specially designed for outdoors are the way to go. The protection classes required for such are part and parcel and different colours and shapes are options. Universal use and not to be overlooked as a security product.

Special features

- Base H x dia.: 12 x 270 mm

Housing Material	Die-cast aluminium	Energy Efficiency Class	G
Housing Color	Gray		
Material of Lens	Plastic		
Protection Class	Protection class I/protective grounding		
Rated Input	30 W		
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	2300 lm		
Rated Angle of Reflection	113 Degree		
Distribution Characteristic	DLS		
120°			
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	50 mm		
Diameter	340 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		
Life Time L70 / B50	30000 h		
Switching Cycles	100000		
Power Consumption	33 kWh/1000h		

