



Versatile and functional - The Mensae LED outside wall and ceiling light boasts an impressive flat design and can be used both indoors and outdoors with its movement sensor including daylight sensor. The white cover atop the dark grey aluminium die-cast frame houses 96 warm white LEDs with 18 watts and 3,000 K.

Housing Material	Die-cast aluminium	Energy Efficiency Class	G
Housing Color	Gray		
Material of Lens	Plastic		
Protection Class	Protection class I/protective grounding		
Rated Input	20 W		
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1340 lm		
Rated Angle of Reflection	110 Degree		
Distribution Characteristic	DLS		
120°			
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top, Below, Side		
Height	48 mm		
Diameter	300 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		
Life Time L70 / B50	30000 h		
Switching Cycles	100000		
Power Consumption	22 kWh/1000h		

