



MENKAR series ceiling lights impress with clever lighting functions and high-quality aluminium accents. The rear light, which can be switched on separately (approx. 15-20 % of indirect lighting component), allows continuous indirect lighting whilst the main light can be switched on at any time.

Special features

- Indirect and direct lighting
- Light colour adjustable in 2 stages
- Indirect lighting can be switched on separately
- Dimmable
- High luminous intensity

Housing Material	Aluminium	Life Time L70 / B50	30000 h
Housing Color	Silver	Switching Cycles	25000
Housing Surface	Brushed	Power Consumption	41 kWh/1000h
Material of Lens	Acryl	Energy Efficiency Class	E
Colour of Lens	White		
Surface Structure of Lens	Opal		
Protection Class	Protection class I/ protective grounding		
Rated Input	41 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	3460 lm		
Rated Angle of Reflection	115 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	2		
Light direction	Below, Top		
Height	90 mm		
Diameter	400 mm		
Working Temperature	-10 to 45 °C		
Storage Temperature	-10 to 45 °C		
IP Protection Class	IP 20		