



Ceiling lights in the LUCEA series are available with or without mount in the 10, 15, 20 and 30 watt output levels. The variants with mount can also be rotated and swivelled. They provide up to 2,900 lumens of light output depending on the design. The light emission angle can be narrowed or expanded by exchanging optionally available lenses.

Special features

- High colour rendering
- Light colour adjustable in 2 stages
- Housing made from die-cast aluminium
- Dimmable

Housing Material	Aluminium	Switching Cycles	100000
Housing Color	White	Power Consumption	15 kWh/1000h
Material of Lens	PMMA	Energy Efficiency Class	F
Protection Class	Protection class I/ protective grounding		
Rated Input	15 W		
Rated Input Voltage min./max. Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	Leading-edge dimmer, Trailing edge dimmer		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1460/1500 lm		
Rated Luminous Flux 2	1500 lm		
Rated Angle of Reflection	36 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	178 mm		
Diameter	85 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 65 °C		
IP Protection Class	IP 20		
Life Time L70 / B50	50000 h		