



Our new SUBRA lights cut a fine figure whether ceiling- or wall-mounted. This is ensured not only by the low assembly height of just 7 cm but also by the circumferential light ring, which functions as an additional design element. The SUBRA offers added sophistication when it comes to dimming. There is TRIAC [analogue] and DALI [digital] to choose from - both for the warm white and neutral white versions. There is also a variant with an integrated, adjustable movement sensor.

Special features

- Light ring as design element
- Easy to install using clip connection
- High light output
- Splash water protected for ceiling installation

Housing Material	Aluminium	IK Protection Class	IK10
Housing Color	White	Life Time L70 / B50	50000 h
Material of Lens	Plastic	Switching Cycles	40000
Colour of Lens	White	Power Consumption	29 kWh/1000h
Protection Class	Protection class II/protective insulation	Energy Efficiency Class	F
Rated Input	29 W		
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	No		
Motion Detector	Yes		
Kind of Motion Detector	Infrared		
Detection Distance	1-10 m		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	2651 lm		
Rated Angle of Reflection	110 Degree		
Light Distribution	Symmetric		
Distribution Characteristic	DLS		
120°			
Light Exit Surfaces	2		
Light characteristics	Direct		
Light direction	Below, Side		
Height	70 mm		
Diameter	350 mm		
Working Temperature	-10 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		