



- Reflections in the most beautiful light: The LINE I and LINE II lights distribute their warm white light extensively and shadow-free onto mirrors up to a thickness of 10 mm. Using the adapter supplied, the LINE series can also function as an elegant surface-mounted lamp for various furniture items as required.

Housing Material	Aluminium	Life Time L70 / B50	30000 h
Housing Color	Silver	Switching Cycles	15000
Housing Surface	Shiny	Power Consumption	8 kWh/1000h
		Energy Efficiency Class	G
Protection Class	Protection class II/protective insulation		
Rated Input	8 W		
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	No		
Connection Cable Primary	Yes		
Primary Connection	Power plug IP20		
Connection Cable Secondary	Yes		
Secondary Connection	Plug mini AMP		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	380 lm		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Depth	312 mm		
Width	100 mm		
Height	67 mm		
Working Temperature	-5 to 40 °C		
Storage Temperature	-10 to 40 °C		
IP Protection Class	IP 44		