



Housing Material	Die-cast aluminium
Housing Color	Yellow
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input	2.2 W
Rated Input Voltage	3.7 V/DC
Power Supply Unit incl.	No
Connection Type	USB type C
Control	Touch and Dim
Motion Detector	No
Accumulator/Battery Operated	Yes
Rechargeable/battery included	Yes
Number of Accumulator/Battery	1
Type of Accumulator/Battery	Li-Ion battery type 18650
Accumulator/Battery Capacity	4400 mAh
Accumulator/Battery Voltage	3.7 V/DC
Accumulator Charging Time	5-7 h
Accumulator Operating Time	12 h

Diameter	120 mm
Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 60 °C
IP Protection Class	IP 54
Life Time L70 / B50	30000 h
Switching Cycles	15000

Light Source	LED, Light source not changeable
Lightcolor	Warm white (WW)
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	196 lm
Luminous Efficiency	89.09 lm/W
Rated Angle of Reflection	47 Degree
Light Distribution	Asymetric
Depth	120 mm
Width	120 mm
Height	300 mm