



Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. The Up and Down version emits its light in two directions. Whilst the LEDs directed upwards generate pleasant, indirect room lighting, the LEDs directed downwards ensure defined, powerful and UGR-compliant office and work lighting for desks and more.

Special features

- High light output
- Low glare value
- Max. suspended mounting 3,000 mm
- Dimmable

Housing Material	Aluminium	IP Protection Class	IP 20
Housing Color	White	Life Time L70 / B50	50000 h
Material of Lens	Plastic	Switching Cycles	25000
Protection Class	Protection class I/protective grounding	Power Consumption	60 kWh/1000h
Rated Input	60 W	Energy Efficiency Class	E
Rated Input Voltage min./max.	200-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	DALI 1 / DT6		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	7180 lm		
Rated Angle of Reflection	110 Degree		
Rated Angle of Reflection 2	24 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Depth	1177.4 mm		
Width	53 mm		
Height	53 mm		
Pendulum Length max.	3000 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-30 to 60 °C		

