



Modular, compact, impactful - The GRUMIUM wall-mounted light can be installed on patios, building walls or in entrances to living spaces and, thanks to its optional covers in different designs, provides a flexible universal solution for many areas of application. The permanently installed and energy-saving LEDs delivering max. 10 watts are encompassed by a diffuser made of milky plastic and produce a pleasant warm white light with a luminous flux of 730 lm. The Grumium outdoor light with die-cast aluminium housing comes in an angular and rounded design and has degree of protection IP54.

Special features

- Can be customised using replaceable add-ons
- Warm white/cold white can be selected using a switch

Housing Material	Die-cast aluminium	Switching Cycles	15000
Housing Color	Gray	Power Consumption	10 kWh/1000h
Material of Lens	Plastic	Energy Efficiency Class	F
Colour of Lens	White		
Protection Class	Protection class I/protective grounding		
Rated Input	10 W		
Rated Input Voltage min./max.	220-240 V/AC 50 / 60 Hz		
Frequency			
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Control	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	205 lm		
Rated Angle of Reflection	138 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	3		
Light characteristics	Direct		
Light direction	Top, Below, Side		
Depth	100 mm		
Width	70 mm		
Height	200 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		
Life Time L70 / B50	30000 h		