



Geometric styling and maximum variability - the YPSILON consists of two parts, a base and exchangeable Y-part. Thanks to the round base and the variable fastening, highly appealing light patterns can be produced on walls with one or more YPSILON lights. Rotating by just a few degrees creates a completely different light pattern. Thanks to the many different materials such as white plaster that allows for further customisation and grey granite, almost impossible variants can be conjured up.

**Special features**

- Indirect light
- Exceptional design
- High colour reproduction value

<b>Housing Material</b>	Aluminium	<b>Power Consumption</b>	4 kWh/1000h
<b>Housing Color</b>	White	<b>Energy Efficiency Class</b>	G
<b>Protection Class</b>	Protection class II/protective insulation		
<b>Rated Input</b>	4 W		
<b>Rated Input Voltage min./max.</b>	220-240 V/AC 50 / 60 Hz		
<b>Frequency</b>			
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	350 lm		
<b>Rated Angle of Reflection</b>	180 Degree		
<b>Distribution Characteristic</b>	NDLS		
<b>120°</b>			
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Indirect		
<b>Light direction</b>	Rear		
<b>Depth</b>	245 mm		
<b>Width</b>	231.8 mm		
<b>Height</b>	65 mm		
<b>Diameter</b>	100 mm		
<b>Working Temperature</b>	-5 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 20		
<b>Life Time L70 / B50</b>	50000 h		
<b>Switching Cycles</b>	25000		