

**Special features**

- Recess and surface mounting possible
- Dimmable

Housing Material	Aluminium
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Plastic
Colour of Lens	White
Surface Structure of Lens	Opal

Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input	2 W
Rated Input Voltage	12 V/DC
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	Power plug
Connection Cable Secondary	Yes
Secondary Connection	Plug mini AMP
Secondary Cable Length	1.5 m
Control	dimmable via optional power supply unit
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	240 lm
Rated Angle of Reflection	110 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	12.5 mm
---------------	---------

Diameter	62 mm
Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	3 kWh/1000h
Energy Efficiency Class	G