



Reflections in the most beautiful light: The Line I and Line II lights distribute their warm white light extensively and shadow-free onto mirrors up to a thickness of 10 mm. Using the adapter supplied, the Line series can also function as an elegant surface-mounted lamp for various furniture items as required.

Housing Material	Aluminium
Housing Color	Silver
Housing Surface	Shiny
Material of Lens	Plastic
Surface Structure of Lens	Structured
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input	4.5 W
Rated Input Voltage	12 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Plug mini AMP
Secondary Cable Length	1.5 m
Control	dimmable via optional power supply unit
Motion Detector	No

Storage Temperature	-10 to 40 °C
IP Protection Class	IP 44
Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	5 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	300 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Depth	96.5 mm
Height	14 mm
Diameter	80 mm

Working Temperature	-5 to 40 °C
----------------------------	-------------