



Equipped with LEDs in a neutral white light colour [4,000 K], the TRIPROOF LED IP65 damp-proof light consists of a light grey polycarbonate housing and a satin-finished polycarbonate cover in one piece. It is suitable for simple ceiling, wall or suspended mounting and is available in three different lengths. Several lights can be connected in series; ideal for industrial and private use, e.g. for lighting under canopies, in cellar rooms, workshops, garages, industrial halls etc. The light has a simple electrical connection with push-in connector.

Special features

- High impact resistance
- Feed-through wiring possible

| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Plastic | Power Consumption | 35 kWh/1000h |
| Housing Color | White | Energy Efficiency Class | G |
| Housing Surface | Matt | | |
| Protection Class | Protection class II/protective insulation | | |
| Rated Input | 35 W | | |
| Rated Input Voltage min./max. | 180-240 V/AC 50 / 60 Hz | | |
| Frequency | | | |
| Power Supply Unit incl. | Yes | | |
| Connection Type | Clamp | | |
| Control | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 4000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 2980 lm | | |
| Rated Angle of Reflection | 120 Degree | | |
| Distribution Characteristic 120° | NDLS | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Depth | 1296 mm | | |
| Width | 61 mm | | |
| Height | 56 mm | | |
| Working Temperature | -20 to 40 °C | | |
| Storage Temperature | -10 to 60 °C | | |
| IP Protection Class | IP 65 | | |
| Life Time L70 / B50 | 35000 h | | |
| Switching Cycles | 15000 | | |

