



The transformation artist - no cable outlet where you need the light to be? No problem for the MOBBY II. Thanks to its swivelling head, areas can be lit up that otherwise wouldn't be reached. The MOBBY II is equipped with the powerful and cost-efficient 9 watt LED module.

#### Special features

- Light emission angle can be changed with optional replaceable reflector

<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Black	<b>Switching Cycles</b>	100000
<b>Protection Class</b>	Protection class I/ protective grounding	<b>Power Consumption</b>	20 kWh/1000h
<b>Rated Input</b>	19.9 W	<b>Energy Efficiency Class</b>	G
<b>Rated Input Voltage min./max. Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	Leading-edge dimmer, Trailing edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	1620 lm		
<b>Rated Angle of Reflection</b>	53 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Depth</b>	84 mm		
<b>Width</b>	124 mm		
<b>Height</b>	220 mm		
<b>Diameter</b>	84 mm		
<b>Working Temperature</b>	-20 to 50 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 55		