



The square JABBAH uses integrated COB LEDs in warm white, emitting its light asymmetrically at an angle of 75° onto walls in a cone of illumination - in a simple variant providing 915 lumens, as an UP AND DOWN version providing a total of 1,850 lumens. In addition, the two-sided JABBAH can be dimmed to 60 % luminous flux using a dip switch, if a more subtle light is desired.

#### Special features

- Modern design
- Dimmable to 60 % using DIP switch
- High luminous flux

<b>Housing Material</b>	Die-cast aluminium	<b>Energy Efficiency Class</b>	G
<b>Housing Color</b>	Gray		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	13 W		
<b>Rated Input Voltage min./max.</b>	220-240 V/AC 50 / 60 Hz		
<b>Frequency</b>			
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	Yes, step-dimmable		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	915 lm		
<b>Rated Angle of Reflection</b>	75 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Depth</b>	150 mm		
<b>Width</b>	150 mm		
<b>Height</b>	150 mm		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 65		
<b>Life Time L70 / B50</b>	30000 h		
<b>Switching Cycles</b>	15000		
<b>Power Consumption</b>	13 kWh/1000h		