



The ALKES series is not a traditional wall-mounted light but reminds you of a floodlight with its SMD-LED panel. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.

#### Special features

- High luminous efficacy
- Homogeneous light distribution
- Die-cast aluminium housing

<b>Housing Material</b>	Die-cast aluminium	<b>Power Consumption</b>	36 kWh/1000h
<b>Housing Color</b>	Gray	<b>Energy Efficiency Class</b>	G
<b>Material of Lens</b>	Glass		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	36 W		
<b>Rated Input Voltage min./max.</b>	220-240 V/AC 50 / 60 Hz		
<b>Frequency</b>			
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Control</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	1720 lm		
<b>Rated Angle of Reflection</b>	110 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Depth</b>	297 mm		
<b>Width</b>	165 mm		
<b>Height</b>	240 mm		
<b>Working Temperature</b>	-20 to 50 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 65		
<b>Life Time L70 / B50</b>	26500 h		
<b>Switching Cycles</b>	15000		