



The new COLT series is a genuine all-rounder outdoors: Powerful, freely rotatable and tiltable and equipped with the latest LED technology, the surface-mounted lamps deliver atmospheric illumination concepts in any outdoor application and cut a fine figure even when switched off thanks to their striking design.

Special features

- Replaceable reflectors
- Including clear/frosted glass pane
- Including honeycomb filter
- Feed-through wiring possible

| | |
|-----------------------------------|---|
| Housing Material | Die-cast aluminium |
| Housing Color | Black |
| Material of Lens | Glass |
| Protection Class | Protection class III/safety extra-low voltage |
| Operating Mode | Voltage constant |
| Rated Input | 3.2 W |
| Rated Input Voltage | 24 V/DC |
| Power Supply Unit incl. | No |
| Connection Cable Secondary | Yes |
| Secondary Connection | WEIPU plug 5-pole |
| Secondary Cable Length | 2 m |
| Control | dimmable via optional controller |
| Motion Detector | No |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 2700 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 80 |
| Rated Luminous Flux | 92 lm |
| Rated Angle of Reflection | 20 Degree |
| Light Distribution | Symmetric |
| Distribution Characteristic 120° | DLS |

| | |
|------------------------------|-----------|
| Swivel Angle | 45 Degree |
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Top |

| | |
|-----------------|-------|
| Height | 65 mm |
| Diameter | 50 mm |

| | |
|----------------------------|--------------|
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -30 to 60 °C |

| | |
|--------------------------------|-------------|
| IP Protection Class | IP 65 |
| Life Time L70 / B50 | 50000 h |
| Switching Cycles | 25000 |
| Power Consumption | 4 kWh/1000h |
| Energy Efficiency Class | G |