



The CATA IV series not only impresses as a modern path light but also as a stand-alone lighting and design feature when creating outdoor spaces. The LEDs not only ensure full-surface illumination of paths and entrance areas but also inevitably draw attention to the striking frame construction. Available in three sizes, the CATA IV models can also be combined really well.

Special features

- Base L x W x H: 145 x 55 x 20 mm

Housing Material	Die-cast aluminium
Housing Color	Anthracite
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	4 W
Rated Input Voltage min./max.	100-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box IP65
Control	No
Motion Detector	No

Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	4 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	170 lm
Rated Angle of Reflection	120 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Depth	151 mm
Width	61 mm
Height	500 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54