



- Special features**
- Including 10 m connecting cable with WEIPU IP67 plug

Housing Material	Stainless steel
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input	3 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	WEIPU plug 2-pole
Secondary Cable Length	10 m
Control	dimmable via optional controller
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	105 lm
Luminous Efficiency	35 lm/W
Rated Angle of Reflection	45 Degree
Rated Angle of Reflection 2	35 Degree
Light Distribution	Asymetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	73 mm
Diameter	68.5 mm
Installation Depth	135 mm
Cut Out Diameter	59 mm

Product weight	810 g
Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 68/max. 2 m
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	3 kWh/1000h
Energy Efficiency Class	G