



- Special features
- High degree of flexibility
 - Can easily be shortened to desired length

Housing Material	Copper
Housing Color	White
Material of Lens	Silicone
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Voltage constant
Rated Input 1m	22.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	1 m
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	1 m
Control	dimmable via optional controller
Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Angle of Reflection	110 Degree
Luminous Flux 1m	2555 lm
Luminous Efficiency 1m	113.56 lm/W
LED/Meter	160
Bending Radius min.	20 mm
Total Length to be Operated max.	5 m
Segment Length	50 mm
Segment LED Quantity	8
LED Distance	6.25 mm
Depth	5000 mm
Width	10 mm

Height	3 mm
Product weight	200 g
Working Temperature	-15 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 44
Type of IP Protection	Silicone
Life Time L70 / B50	60000 h
Switching Cycles	30000
Power Consumption	75 kWh/1000h
Energy Efficiency Class	D